



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Julabo PRESTO W56 High dynamic temperature control system Remark: plus packaging costs /

**Price on
request
plus VAT &
Shipping**

Product Images



Description

The water-cooled PRESTO W56 can temper applications with high power requirements very quickly and efficiently. It has large power reserves even at low temperatures for demanding external applications. The magnetically coupled pump allows the user to optimally adapt the pump performance to the application, even over greater distances and heights as well as in pressure-sensitive applications. By using the latest thermodynamic technologies, the cooling capacity is automatically adapted to the current power requirement. In combination with further optimizations, the PRESTO W56 operates very economically and energy-efficiently. Pump type: centrifugal pump Product features: - Pt100 external sensor connection - Analog connections, RS485, Profibus DP (accessories) - Second Pt100 external sensor connection (accessories) - Pump pressure up to 3.2 bar, max. 80 l/min flow rate - Cooling capacity up to 25 kW - Heating capacity up to 27 kW - Temperature constancy $\pm 0.05 \dots \pm 0.1^\circ\text{C}$ - Alarm output - Integrated 5.7" color industrial touch screen - Connections for USB, Ethernet, RS232, Modbus Cooling capacity: Capacity data measured according to DIN 12876. Cooling capacities up to 20 °C measured with ethanol, above 20 °C measured with thermal oil, unless otherwise stated. Performance data apply at an ambient temperature of 20 °C. Performance values may deviate with other temperature control liquids.

Additional Information

No.	JN-0772
Manufacturer (Brand)	Julabo
EAN	4058072848347
Transport temperature	Room temperature
Net weight	385.00000 kg
Country of origin	Germany
Customs tariff number	84198998

