



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



neolab® drying oven, stainless steel, forced convection, 220 L, 300 °C

**€3,165.00
plus VAT &
Shipping**

Product Images



Description

The **neoLab laboratory drying ovens** are suitable for thermal processes for materials up to 350 °C: Drying, heating, thermal testing and aging control in an appropriate environment. The drying ovens can be used in scientific laboratories, schools and other educational institutions, in medicine and in industry. The drying ovens with hermetically sealable doors have a high degree of accuracy and are therefore the economical solution for all standard applications.

- short heating and cooling times
- with overtemperature protection and digital timer
- forced air circulation ensures homogeneous temperature distribution
- made of stainless steel
- NO adjustable fan speed
- shelves included

Additional functions optionally available

- programmable temperature controller
- Computer Softwar (Windows) for data monitoring, transmission and recording (up to 8 PCs)
- Buzzer

Additional Information

| | |
|---------------------------------------|--|
| No. | 7-9343 |
| Manufacturer (Brand) | neoLab |
| EAN | 4058072195144 |
| Transport temperature | Room temperature |
| autoclavable at 121°C | No |
| Color | gray silver |
| Temp MAX | 300 °C |
| Temp MIN | 20 °C |
| Volume | 220 l |
| sterile | No |
| Wide | 875 mm |
| Width/inside | 500 mm |
| Height | 915 mm |
| Height inside | 620.0 mm |
| Length | 930 mm |
| Depth | 930 mm |
| Depth inside | 730 mm |
| Number of shelves/ grids | 7 |
| Operation via | Membrane keypad knobs/keys |
| Weight | 102 kg |
| Length inside | 730 mm |
| Voltage | 230 V |
| Heaters and warming cabinets features | with overheating protection with certification |
| Type of convection | Circulating air |
| Power | 4000 W |
| Material inside | Stainless steel |
| Page door suspension | right |

| | |
|------------------------------------|---|
| Positioning variants | single |
| Temp MIN above ambient temperature | 10 °C |
| Temp. accuracy | +/- 0.3 °C |
| Type tempering cabinet | Drying cabinet |
| Type certificate | Declaration of conformity (standardization) |

