



neolab Migge GmbH  
Rischerstr. 7-9  
69123 Heidelberg  
Deutschland  
+49 (0)6221 /  
8442-44  
<https://www.neolab.de>  
e

Umsatzsteuer-  
Identifikationsnummer  
:  
DE 143 450 657



## 2mag magnetic stirrer 500 ml to 40 l, stainless steel, 60-2000 rpm

**€1,324.00**  
**plus VAT &**  
**Shipping**

### Product Images



## Description

---

**Ultra-flat, very powerful magnetic stirrer with large footprint** and

fully automatic stirring rod monitoring mixWATCH, also suitable for highly viscous media.

Predestined for power transmission over longer distances or for thick vessel bottoms.

Maintenance-free drive with wide speed range.

Encapsulated easy-care stainless steel housing, easy to clean and maximally durable.

**Integrated control** with 20 watt stirring power, 4-stage power setting for high power with large and viscous stirring quantities and reduced power for continuous operation without heating.

4-fold variable SoftStart function for reliable catching/centering and safe acceleration of the stirring staff.

Adjustable interval times for automatic restart.

Digital display for speed, power, SoftStart and interval setting, QuickSet for fast setting of initial or maximum speed,

QuickStop function against overrun and glass breakage, saving of last function status when switched off.

Stirring staff monitoring with automatic adjustment of max. achievable speed for reliable unattended operation of the stirrer.

Technical data

Stirring power: 5/10/15/20 watts (4-stage)

Acceleration: 20/30/60/120 seconds, stages adjustable

Interval: 0-240 sec., stages adjustable (2-step)

Weight: approx. 4.0 kg

Mains connection: 100-240 V / 50-60 Hz / 1.5 A

## Additional Information

No.	ZU-0006
Manufacturer (Brand)	2mag
old neoLab article no.	7-3088
EAN	4058072444440
Transport temperature	Room temperature
Speed MAX	2000 rpm
Color	silver
Material	Stainless steel
Wide	225 mm
Height	35 mm
Depth	280 mm
Display (reading, setting)	digital
Weight	4 kg
Voltage	230 V
for ambient temperature	-10 to 50 °C
Stirrers and rotators features	ultraflat with infinitely variable speed control with timer
Number of speed levels	4
Number of stirring points	1
Speed MIN	60 rpm
Magnetic stirrer power	20 W
Material housing	Stainless steel
Material stirring plate	Stainless steel
Maximum relative humidity at 20 °C	80.0 %
Model magnetic stirrer	neoLab magnetic stirrer up to 40 l (7-3088)
Stirring power/ Stirring point	20 W
Stirring volume/stirring point MAX	40 l
Stirring volume/ stirring point MIN	500 ml

Protection class

IP 64

Temperature sensor

without

