



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



2mag magnetic stirrer with 6 stirring positions, 1-3 l, 100-2000 rpm

€1,779.00
plus VAT &
Shipping

Product Images



Description

Stainless steel multi-position stirrer with integrated control

For reliable serial testing as well as for chemical, biotechnical and medical applications of all kinds.

Ultra-flat, wear-free magnetic stirrer with 100% wear- and maintenance-free induction drive for powerful mixing of solutions.

Wide speed range from 100 to 2,000 rpm, 100% synchronous rotation, jerk-free stirring even at low speeds. Power setting (4-stage) for high power for large and viscous stirring quantities and reduced power for continuous operation without heating.

Digital display for speed and power setting, SoftStart for reliable catching/centering and safe acceleration of the stirring staff, memory of the last functional state when switched off, fully potted stainless steel housing, easy to clean and durable.

Additional Information

No.	ZU-0002
Manufacturer (Brand)	2mag
old neoLab article no.	7-3085
EAN	4058072444402
Transport temperature	Room temperature
Speed MAX	2000 rpm
Color	silver
Material	Stainless steel
Wide	245 mm
Height	38 mm
Depth	425 mm
Display (reading, setting)	digital
Weight	8.8 kg
Voltage	230 V
for ambient temperature	-10 to 50 °C
Stirrers and rotators features	ultraflat with infinitely variable speed control
Speed MIN	100 rpm
Number of speed levels	stepless
Number of stirring points	6
Material housing	Stainless steel
Magnetic stirrer power	120 W
Material stirring plate	Stainless steel
Maximum relative humidity at 20 °C	80.0 %
Model magnetic stirrer	2mag MIX 6
Stirring power/ Stirring point	20 W
Stirring volume/stirring point MAX	3000 ml
Stirring volume/ stirring point MIN	1 ml

