



neolab Migge GmbH  
Rischerstr. 7-9  
69123 Heidelberg  
Deutschland  
+49 (0)6221 /  
8442-44  
<https://www.neolab.de>  
e

Umsatzsteuer-  
Identifikationsnummer  
:  
DE 143 450 657



## 2mag magnetic stirrer with 15 stirring positions, 1-1.5 l, 120-1,200 rpm

**€1,177.00**  
**plus VAT &**  
**Shipping**

### Product Images



## Description

---

### **Stainless steel multi-position stirrer with integrated control**

For reliable serial testing as well as for chemical, biotechnical and medical applications of all kinds.

Ultra-flat, wear-free magnetic stirrer with 100% wear- and maintenance-free induction drive for powerful mixing of solutions.

Wide speed range from 100 to 2,000 rpm, 100% synchronous rotation, jerk-free stirring even at low speeds. Power setting (4-stage) for high power for large and viscous stirring quantities and reduced power for continuous operation without heating.

Digital display for speed and power setting, SoftStart for reliable catching/centering and safe acceleration of the stirring staff, memory of the last functional state when switched off, fully potted stainless steel housing, easy to clean and durable.

## Additional Information

No.	ZU-0005
Manufacturer (Brand)	2mag
old neolab article no.	7-3087
EAN	4058072444433
Transport temperature	Room temperature
Speed MAX	1200 rpm
Color	silver
Material	Stainless steel
Wide	245 mm
Height	38 mm
Depth	425 mm
Display (reading, setting)	digital
Weight	8.8 kg
Voltage	230 V
for ambient temperature	-10 to 50 °C
Stirrers and rotators features	ultra-flat with infinitely variable speed control with automatic speed adjustment in case of viscosity change
Number of speed levels	stepless
Number of stirring points	15
Speed MIN	120 rpm
Magnetic stirrer power	150 W
Material housing	Stainless steel
Material stirring plate	Stainless steel
Maximum relative humidity at 20 °C	80.0 %
Model magnetic stirrer	2mag MIX 15 eco
Stirring power/ Stirring point	10 W
Stirring volume/ stirring point MAX	1500 ml
Stirring volume/ stirring point MIN	1 ml

Protection class

IP 64

Temperature sensor

without

