

neoLab Migge GmbH Rischerstr. 7-9 69123 Heidelberg Deutschland +49 (0)6221 / 8442-44 https://www.neolab.d e Umsatzsteuer-Identifikationsnummer :

DE 143 450 657



KERN analytical balance ABP, 102 g | 220 g

€3,400.00 plus VAT & Shipping

Product Images



Description

- NEW: Extremely fast ionization process, thanks to the latest generation of KERN ionization technology for neutralizing electrostatic charge for fixed installation in the analytical balance. Particularly convenient handling, as a separate device is no longer necessary. Simply switch on the ionization blower by pressing a button. Suitable for all models in this series
- High-brightness OLED display with large viewing angle stability for optimal readability from different viewing directions
- RS-232 and USB data interfaces for transferring weighing data to PC, tablet, printer as well as for connecting external devices, such as barcode scanner (option), numeric keyboard (option), etc.
- GLP/ISO protocol: professional and detailed GLP protocol, thus the balance is fully compliant with the relevant standard requirements according to ISO, GLP and GMP
- This new generation of analytical balances combines highest precision with large weighing ranges. Thanks to the new single-cell generation, the weighing result is displayed in a fraction of the time of comparable models. Together with the intuitively designed menu, this ensures efficient and fast operation
- Navigation cross for lightning-fast navigation within the menu
- Internal automatic calibration for temperature changes > 1 °C and time-controlled every 4 h, guarantees high accuracy and makes the balance location-independent
- The minimum sample weight can be stored manually in the instrument or calculated automatically. When weighing below this value, the balance issues a warning message
- Dosing aid: High stability mode and other filter settings can be selected
- Convenient formulation/documentation with combined tare/print function. In addition, the mixture ingredients of the recipe are automatically numbered and printed out with number/weight value
- Individual user settings can be stored for up to 10 users: User name/number (can be printed out for each process or saved to the data record), password, menu language, user profiles, access to user settings via barcode, additional guest mode for users who are not logged in, authorizations, e.g. scale adjustment, change of settings or creation or modification of a recipe only by the authorized person & execution of formulation by the user
- U.S. FDA 21 Part 11: Supports data integrity according to U.S. FDA 21 Part 11 (e.g. weighing result, sample ID, user name, scale ID etc.)
- Menu language DE, GB
- Automatic data output to PC/printer after each stability of the scale
- Large glass draft shield with 3 sliding doors for comfortable access to the sample
- Multifunctional weighing plate included in the scope of delivery minimizes the effect of air currents in the weighing chamber and thus significantly improves settling time and repeatability. In addition, protruding samples, sample paper, PCR tubes, microcentrifuge tubes, etc. can be conveniently fixed in place and weighed with ease
- Protective hood included in delivery

Single-cell cutting-edge technology:

- Fully automatic production of the load cell from one piece
- Stable temperature behavior
- Short settling time: Stable weighing values within approx. 2 sec (models with = 0.1 mg), approx. 8 sec (models with = 0.01 mg) under laboratory conditions
- High mechanical robustness
- High corner load stability

Additional Information

| No. | KP-1689 |
|-------------------------|--------------------------------|
| Manufacturer (Brand) | KERN |
| EAN | 4058072128463 |
| Transport temperature | Room temperature |
| Color | light grey grey |
| Wide | 595 mm |
| Height | 380 mm |
| Depth | 380 mm |
| Readability | 0,1 mg |
| Operation via | Membrane keypad |
| Weight | 11.23 kg |
| Reproducibility | 0,02 mg |
| Scales features | with switchable weighing units |
| Material weighing plate | Stainless steel |
| Weighing range MAX | 102 g |
| Manufacturer | CORE |
| Type scale | Analytical balance |

