



Julabo CF40 Cryo-Compact Thermostat

Product Images



Description

Cryocompact thermostats of the CF series are extremely compact refrigerated circulators. The devices offer 2 kW heating capacity as well as protection class III according to DIN 12876-1. They have pump connections for external temperature control applications as well as a bath opening for temperature control of smaller objects. Bath vessel: stainless steel Bath cover: integrated Medium bath opening (cm/WxD/BD): 19 x 3 / 19 Pump type: submersible pump Product features: - Particularly compact dimensions for low space requirements - Splash-proof membrane keypads - Large, bright LED temperature display - Precise PID temperature control - RS232 interface for PC connection - Classification 3 according to DIN12876-1 - Pump connections for external temperature control tasks -

Bath opening for temperature control of small objects directly in the thermostat bath - Drain cock on the front Scope of delivery: 2 hose olives each suitable for hose 8 and 12 mm I.W. (pump connections with M16x1 male thread) Cooling capacity: Capacity data measured according to DIN 12876. Cooling capacities up to 20 °C measured with ethanol, above 20 °C measured with thermal oil, unless otherwise stated. Performance data apply at an ambient temperature of 20 °C. Performance values may deviate with other temperature control fluids.

Additional Information

No.	JN-0484
Manufacturer (Brand)	Julabo
EAN	4058072848200
Net weight	44.00000 kg
Temp MAX	150 °C
Temp MIN	-40 °C
Country of origin	Deutschland
Customs tariff number	84198998

