



Julabo FC600 Recirculating Cooler

Product Images



Description

The recirculating coolers of the FC series feature an increased operating temperature range thanks to their integrated heater. They operate very precisely with a temperature constancy of ± 0.2 °C. Bath vessel: Stainless steel Pump type: Submersible pump Product features: - Flow and return temperature adjustable in ratio (DBGM) - Easy filling due to front-mounted filling system - Activation of circulation pump during filling process - Luminous MULTI-DISPLAY (LED) for actual/setpoint value - Over/under temperature warning functions with interval signal tone - Integrated freeze protection and dry-running protection - Quick and safe to operate membrane

keypad - Level indication via sight glass on the front - Self-test, Sensor operation monitoring, pump motor and compressor protection - All-pole disconnection with acoustic indication in case of alarm - Removable ventilation grille for easy removal of unavoidable dust - RS232 interface for PC connection - High temperature constancy - Integrated heater with 1.2 kW heating capacity - Delivery pressure display Scope of delivery: 2 hose olives each suitable for 8 and 12 mm I.w. hose (pump connections with M16x1 male thread) Refrigeration capacity: Capacity data measured according to DIN 12876. Refrigeration capacities up to 20 °C measured with ethanol, above 20 °C measured with thermal oil, unless otherwise stated. Performance data apply at an ambient temperature of 20 °C. Performance values may deviate with other temperature control fluids.

Additional Information

| | |
|-----------------------|---------------|
| No. | JN-0509 |
| Manufacturer (Brand) | Julabo |
| EAN | 4058072848590 |
| Net weight | 48.00000 kg |
| Temp MAX | 80 °C |
| Temp MIN | -20 °C |
| Country of origin | Deutschland |
| Customs tariff number | 84198998 |

