



Julabo FL1201 recirculating chiller

Product Images



Description

The compact FL recirculating chillers are suitable for a wide range of cooling tasks and can be installed under the laboratory bench to save space. Air-cooled (FL) and water-cooled (FLW) models are available. Bath vessel: stainless steel Pump type: centrifugal pump

Product features: - Ergonomic design and easy operation - Splash-proof membrane keypads - Large, bright LED temperature display - Reliable microprocessor PID temperature control - Continuously operating, powerful submersible pumps - Permissible return temperature +80°C - Easy filling and easy-access drain cock for easy draining - Low-level protection with visual and audible signal - Integrated stainless steel bath tanks - Easy-access drain cock on front - No side vents: Units can be placed side by side - RS232 interface for PC connection - IP class according to IEC 60529: 21 - Alarm output, potential-free changeover contact (max. 30 VA)

Scope of delivery: 2 hose olives each suitable for hose 8 and 12 mm l.w. (pump connections with M16x1 male thread)

Cooling capacity: Performance data measured according to DIN 12876. Cooling capacities up to 20 °C measured with ethanol, above 20 °C measured with thermal oil, unless otherwise stated. Performance data apply at an ambient temperature of 20 °C. Performance values may deviate with other temperature control fluids.

Additional Information

No.	JN-0533
Manufacturer (Brand)	Julabo
VGKL number	103591201
EAN	4058072848811
Net weight	78.00000 kg
Country of origin	Deutschland
Customs tariff number	84198998

