



Julabo FLW20006 recirculating chiller

Product Images



Description

The most powerful FL recirculating chillers are suitable for a wide range of cooling tasks in the industrial sector, e.g. for dissipating process heat in large systems and plants. Air-cooled (FL) and water-cooled (FLW) models are available. Bath vessel: stainless steel

Pump type: centrifugal pump Product features: - Ergonomic design and easy operation - Splash-proof membrane keypads - Large, bright LED temperature display - Permissible return temperature +80°C - Easy filling from the top due to hinged filling opening - Low-level protection with visual and acoustic signal - Integrated stainless steel bath vessels - Easily accessible drain cock on front - No side vents: Units can be placed side by side - RS232 interface for PC connection - IP class according to IEC 60529: 21 - Alarm output, potential-free changeover contact (max. 30 VA) - Delivery pressure display Scope of delivery: 2 hose olives for hose 1" I.W. (pump connections with G1 1/4 external thread). Cooling capacity: Capacity data measured according to DIN 12876. Cooling capacities up to 20 °C measured with ethanol, above 20 °C measured with thermal oil, unless otherwise stated. Performance data apply at an ambient temperature of 20 °C. Performance values may deviate with other temperature control fluids.

Additional Information

No.	JN-0552
Manufacturer (Brand)	Julabo
EAN	4058072849009
Net weight	341.00000 kg
Country of origin	Deutschland
Customs tariff number	84198998

