



Julabo FP55-SL cryogenic circulator

Product Images



Description

Low temperature circulators with the thermostat SL convince with high heating, cooling and pumping capacities and are used for external temperature control tasks. Bath cover: integrated Product features: - LCD DIALOG DISPLAY for interactive operator guidance

in plain text - ICC temperature control (Intelligent Cascade Control), self-optimizing - TCF temperature control features for optimization of control behavior - RS232/RS485 interface for online communication - Integrated programmer for 6 x 60 program steps - Stakei sockets for cooling water solenoid valve and HSP booster pump - Proportional cooling capacity control Scope of delivery: 2 hose olives each suitable for hose 8 and 12 mm I.W. (pump connections with M16x1 external thread) 2 hose olives each for hose 8 and 12 mm I.W. (pump connections with M16 x 1 external thread). Cooling water connection G 3/4 external with hose olive for hose 1/2 I.W. Cooling capacity: Capacity data measured according to DIN 12876. Cooling capacities up to 20 °C measured with ethanol, above 20 °C measured with thermal oil, unless otherwise stated. Performance data apply at an ambient temperature of 20 °C. Performance values may deviate with other temperature control fluids.

Additional Information

No.	JN-0467
Manufacturer (Brand)	Julabo
EAN	4058072848033
Net weight	180.00000 kg
Temp MAX	100 °C
Temp MIN	-60 °C
Country of origin	Deutschland
Customs tariff number	84198998

