



neoLab Migge GmbH  
Rischerstr. 7-9  
69123 Heidelberg  
Deutschland  
+49 (0)6221 /  
8442-44  
<https://www.neolab.de>  
e

Umsatzsteuer-  
Identifikationsnummer  
:  
DE 143 450 657



## Thermo Scientific Bath Heat/Circulation Thermostat with PPO Bath 3-5 l, 2 kW

**€1,620.00**  
plus VAT &  
Shipping

### Product Images



## Description

---

The cost-effective alternative to stainless steel!

Stable baths made of polyphenylene oxide (PPO), applicable for temperatures up to 100°C.  
They offer exceptional temperature stability at low initial cost.

Temperature range: Rt +13°C to +100°C

Bath opening D x W x L:

E-6101: 130 x 125 x 120 mm

The baths are equipped with the immersion circulator SC100 as standard :

Temperature constancy:  $\pm 0.02$  K

Heating capacity: 2 kW

Circulation capacity: 17 l/min

Max. Pressure: 300 mbar

Safety class: 1/NFL

Further models and various accessories on request!

Accessories: Water line cooling coil for SC 100 (Order No. E-6079 and E-6087)

## Additional Information

No.	LD-4224
Manufacturer (Brand)	Thermo Scientific
old neoLab article no.	E-6101
EAN	4058072287757
Temp MAX	100 °C
Wide	395 mm
Height	360 mm
Length	187 mm
Depth	187 mm
Operation via	Membrane keypad
Weight	5.1 kg
Voltage	230 V
Water baths and thermostats properties	with overheating protection with circulation function cooling coil available as accessory
MAX operating pressure	0.3 bar abs.
Application thermostat (temp. range)	Heat thermostat
Energy supply	Power grid
MAX flow rate [l/min]	17 l/min
Heating capacity	2000 W
Material bath	Polyphenyl oxide (PPO)
Bath depth	130 mm
Bath opening	120 x 125 mm
Volume water bath	3 to 5 l
Material inside	Polyphenyl oxide (PPO)
Temp MIN above ambient temperature	13 °C
Type refrigerator	Thermostat
Cooling type	external
Type thermostat (construction)	Bath thermostat

