



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Thermo Scientific Safe 2020 Class II Biological Safety Cabinets

**Price on
request
plus VAT &
Shipping**

Product Images

Description

Safe 2020 Class II Biological Safety Cabinets Protect your samples in research laboratories, pharmaceutical and control laboratories, pharmacies and hospitals with Safe 2020 Class II Biological Safety Cabinets. Internal depth (metric): 46.5 cm Electrical requirements: 230 V, 50/60 Hz Exhaust filter: H14 HEPA EN 1822 Filter efficiency: 99.995% at most penetrating particle size (MPPS) Filter type: H14 HEPA EN 1822, 99.995% at most penetrating particle size (MPPS) Heat output (Anglo-American): 200w Outer height (metric): 158.6 cm Interior height (metric): 78 cm Hertz: 50/60 Hz Exterior length (metric): 80 cm Illumination: >850 lx Load capacity (Anglo-American): £ 110 Load capacity (metric): 51 kg Net weight (metric): 200 kg Service mount: Up to 4 through access ports; up to 6 on rear panel Shipping weight (metric): 225 kg Certification/Compliance: EN 12469 Height (Anglo-American): 30.7 in. (interior), 62.4 in. (exterior) Height (metric): 158.6 cm (outdoor), 78 cm (indoor) Noise level: 56 or 58 dbA, model-dependent Outlets: one double outlet per side panel Connections: 4 duct penetrations (2 in each side panel) Power consumption: 200 w Window opening: 20 cm; 77.3 cm maximum Window opening (metric): 20 cm Type: II Exhaust volume (metric): 386 m3 (227 CFM)/h Exterior width (anglo): 51.1 in. Inside width (anglo): 4 ft . Outside width (metric): 130 cm Inside Width (metric): 120 cm Unit Size: Each

Additional Information

No.	LD-1455
Manufacturer (Brand)	Thermo Scientific
EAN	4066292011991
Gross weight	225
Transport temperature	Room temperature
Width/inside	120 mm
Height inside	780.0 mm
Voltage	230 V

