



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Thermo Scientific Safe 2020 Class II Biological Safety Cabinets

**Price on
request
plus VAT &
Shipping**

Product Images

Description

Safe 2020 Class II biological safety cabinets Protect your samples in research laboratories, pharmaceutical industry and control laboratories, pharmacies and hospitals with Safe 2020 Class II biological safety cabinets. Electrical requirements: 230 V, 50/60 Hz Exhaust filter: H14 HEPA EN 1822 Filter efficiency: 99.995 % at most penetrating particle size (MPPS) Filter type: H14 HEPA EN 1822, 99.995 % at most penetrating particle size (MPPS) Heat output (Anglo-American): 160 w Hertz: 50/60Hz Outer length (metric): 80cm Illumination: > 800 LX Load capacity (Anglo-American): £ 110 Load capacity (metric): 51kg Maintenance bracket: Up to 4 through access ports, up to 6 on rear panel Shipping weight (metric): 190kg Certification/Compliance: EN 12469 Height (Anglo-American): 30.7 in. (interior), 62.4 in. (exterior) Height (metric): 158.6 cm (outdoor), 78 cm (indoor) Noise level: 56 or 58dbA , depending on model Outlets: one double outlet per side panel Connections: 4 duct penetrations (2 in each side panel) Power consumption: 160w Window opening: 20cm ; 77.3cm max Window opening (metric): 20cm Type: II Exhaust Volume (metric): Powder; Rehydrated to 50L Exterior width (anglo): 39.3 in. Inside width (anglo): 3 ft . Outer Width (metric): 100cm Unit Size: Each

Additional Information

No.	LD-1454
Manufacturer (Brand)	Thermo Scientific
EAN	4066292011984
Gross weight	190
Transport temperature	Room temperature
Net weight	170.00000 kg
Wide	1000 mm
Width/inside	900 mm
Height	1586 mm
Height inside	780.0 mm
Length	800 mm
Depth inside	465 mm
Voltage	230 V

