



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



**CARLO ERBA safety workbench SafeFAST XXL
Premium 2.2m useful dimensions:
2256x1000x1000mm**

**Price on
request
plus VAT &
Shipping**

Product Images

Description

SafeFAST XXL workbench

The SafeFAST XXL is an individualized microbiological safety workbench designed, among other things, to accommodate automated laboratory robots. The workbench offers pure air of class ISO 3 according to ISO EN 14644-1, operates in negative pressure with an inflow barrier of 0.5 m/s air velocity and thus offers maximum product and personal protection. Part of the air is exhausted through an exhaust air HEPA filter to ensure environmental protection. The XXL workbench from FASTER can be "customized" in various ways to meet the requirements of the specific application. Of course, always according to EN 12469:2000. In addition, all XXL models allow working with large and heavy equipment such as 3D printers or robots due to their heavy-duty floors. The standard working depth is 1 m and the working height is 1 m.

Features:

- Epoxy powder coated steel outer case and inner back panel
- Reinforced AISI 304L stainless steel work surface as standard, perforated work surface or work tray available as options
- Filtration by H14 HEPA vertical flow and exhaust filters according to CEN EN 1822
- Ventilation by electric centrifugal fan
- Front and side windows made of safety glass
- Front panel with hinges to hold it open for an opening height up to 600 mm
- Electrical sockets with IP 55 protection
- DEHS test ports (quick couplings) for filter integrity tests
- Lighting by LED outside the working area
- Microprocessor control with alarms for the main unit parameters
- Electronic direct current (DC) blowers

Standard equipment:

- Hinged front window for optimal cleaning
- 1 or 2 sockets depending on the size

Optional equipment:

- Units completely made of stainless steel AISI 304 or 316
- Additional data outlets
- UV light installed on an aluminum night cover
- Side outlets
- Customized dimensions

Model / Type Standards Dimensions W*H*D (mm) Usable dimensions W*H*D (mm) Inflow (m/s) Downflow (m/s) Elec. connection	SafeFASTXXL 1.2 m EN12469, EN61010-1 1233 × 1885 × 1190 1190 × 1000 × 1000 0.45 0.32 230 V 50 Hz	SafeFASTXXL 1.5 m EN12469, EN61010-1 1637 × 1855 × 1190 1495 × 1000 × 1000 0.45 0.32 230 V 50 Hz	SafeFASTXXL 1.8 m EN12469, EN61010-1 1942 × 1885 × 1190 1800 × 1000 × 1000 0.45 0.32 230 V 50 Hz	SafeFAST XXL 2.2 m EN12469, EN61010-1 2398 × 1885 × 1190 2256 × 1000 × 1000 0.45 0.32 230 V 50 Hz

Additional Information

No.	LK-0417
Manufacturer (Brand)	CARLO ERBA
EAN	4058072990046

