



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Eppendorf Centrifuge 5430 R, cooled, without rotor, rotary knobs

€7,391.00
plus VAT &
Shipping

Product Images



Description

The unique Centrifuge **5430 and 5430 R** models combine the advantages of microcentrifuges (small footprint) and benchtop centrifuges (versatility) in one instrument. Rotors for Eppendorf tubes and PCR strips are used in these centrifuges, as usually expected from microcentrifuges. However, that is not all. Despite their compact size, the Centrifuge 5430 and 5430 R hold rotors for microplates and conical 15/50 mL tubes. Now, additional Eppendorf ^{QuickLock®} rotors have been added to the rotor program. These include 48-place rotors (1.5/2.0 mL), a 16-place rotor for Eppendorf ^{Tubes®} 5.0 mL and a swing-out rotor (24 × 1.5/2.0 mL). Their unbeatable versatility makes the Centrifuge 5430 and Centrifuge 5430 R the flagship of Eppendorf microcentrifuges.

Model 5430 is also available as a refrigerated version (5430 R). Since the compressor is located at the rear of the Centrifuge 5430 R—which is the case with all Eppendorf microcentrifuges—only little floor space is required and the access height is kept low.

Additional Information

No.	VB-1957
Manufacturer (Brand)	Eppendorf
old neoLab article no.	E-0822
EAN	4058072420017
Transport temperature	Room temperature
Speed MAX	17500 rpm
Color	White
Temp MAX	40 °C
Temp MIN	-11 °C
Wide	640 mm
Height	290 mm
Length	380 mm
Depth	380 mm
Operation via	Knobs/Buttons
Weight	56 kg
Voltage	230 V
Type interface	USB
for ambient temperature	10 to 40 °C
Centrifuges properties	programmable with timer with interface with continuous function rotor is replaceable (additional) rotors are available as accessories
Speed MIN	100 rpm
Number of speed levels	> 10
Power	1050 W
Maximum relative humidity at 20 °C	75.0 %
Model centrifuge	Eppendorf. 5430 R
RZB	30130 g
Type centrifuge	Table centrifuge (large)

