



neolab Migge GmbH  
Rischerstr. 7-9  
69123 Heidelberg  
Deutschland  
+49 (0)6221 /  
8442-44  
<https://www.neolab.de>  
e

Umsatzsteuer-  
Identifikationsnummer  
:  
DE 143 450 657



## Eppendorf (IVD) Centrifuge 5910 R, cooled, with rotor S-4x400, incl. round beaker and adapter for 5/15/50 mL conicals, membrane keypad

**Price on  
request**

**plus VAT &  
Shipping**

### Product Images



## Description

---

The **5910 R centrifuge** combines a high capacity of up to 4 × 750 mL with exceptional flexibility. Its main swing-out rotor accepts both conical tubes and plates – no need to exchange rotor buckets or adapters. This improves handling and saves time. It is equipped with a powerful cooling system with state-of-the-art temperature management so you can safely centrifuge your samples.

### **Low access height for easy operation**

The 5910 R centrifuge has been designed with a particularly low access height. This not only allows easy loading and unloading, everyone in the lab can also easily reach the open centrifuge lid.

### **Softtouch lid closure**

No unnecessary force is required when closing the centrifuge lid. The soft-touch lid closure makes it easy to close the centrifuge.

### **State-of-the-art operating system and temperature management**

- ' Menu-guided multilingual operation with backlighting
- ' FastTemp<sup>pro</sup>® function for pre-cooling programmable by day and time; in combination with the ECO shut-off function, this significantly reduces power consumption
- ' Dynamic compressor control for precise cooling performance

### **Swing-out rotor with exceptional versatility**

With the large S-4xUniversal swing-bucket rotor, tubes and plates can be used simultaneously by replacing the adapter instead of the rotor bucket.

#### **Your advantages:**

- ' Time-saving: no need to exchange buckets
- ' Cost-saving: no need for separate plate buckets
- ' Space-saving: no need to store different buckets

In addition, selected conical tubes and plate formats can be used with the three new innovative 'universal adapters':

- ' Eppendorf<sup>Tubes</sup>® 5.0 mL/15 mL conical/DWP
- ' 50 mL conical/MTP
- ' 50 mL conical/250 mL/MTP

#### **Your convenience:**

Even more convenience when using conical tubes and plates.

## Additional Information

No.	VB-2379
Manufacturer (Brand)	Eppendorf
old neoLab article no.	E-2012
EAN	4058072424121
Transport temperature	Room temperature
Speed MAX	14000 rpm
Color	White
Temp MAX	40 °C
Temp MIN	-11 °C
sterile	No
Wide	660 mm
Height	370 mm
Length	720 mm
Depth	720 mm
Operation via	Membrane keypad
Weight	109 kg
Voltage	230 V
Centrifuges properties	programmable with timer with cooling with continuous function including rotor(s) rotor is autoclavable rotor is exchangeable (Additional) rotors are available as accessories
Speed MIN	100 rpm
Number of speed levels	> 10
Power	1650 W
Number of rotors supplied	1
Material rotor	Aluminum
Maximum relative humidity at 20 °C	75.0 %
Model centrifuge	Eppendorf. 5910 R
RZB	22132 g

Type rotor

Swing-out rotor

Type centrifuge

Table centrifuge (large)

