



neolab Migge GmbH  
Rischerstr. 7-9  
69123 Heidelberg  
Deutschland  
+49 (0)6221 /  
8442-44  
<https://www.neolab.de>  
e

Umsatzsteuer-  
Identifikationsnummer  
:  
DE 143 450 657



## KERN Leeb hardness tester Max 960, Min 170, d=1 HB,HL,HRB,HRC,HV,MPa

**€2,020.00**  
**plus VAT &**  
**Shipping**

### Product Images



## Description

---

Innovative touchscreen Automatic sensor recognition when connected to the HMO. Mobility: The SAUTER HMO. offers maximum mobility and flexibility of use compared to stationary table-top instruments and hardness testers with internal sensor Tests in all test directions (360°) thanks to an automatic compensation function USB interface for connection to printer and for recharging the battery Hardness comparison block included Internal data memory for up to 500 values Mini statistics function: displays measured value, average value, difference between maximum and minimum value, date and time Measured value display: Rockwell (B & C), Vickers (HV), Brinell (HB), Shore (HSD), Leeb (HL), Tensile strength (MPa) Automatic unit conversion: the measurement result is automatically converted into all mentioned hardness units Supplied in rugged carrying case Technical data Precision: 1 % 800 HLD ( $\pm 6$  HLD) Tensile strength measuring range: 375-2639 MPa (steel) Smallest test weight on solid base: sensor D + DC: 3 kg sensor G: 15 kg Thinnest measurable layer: sensor D + DC: 8 mm sensor G: 10 mm Smallest radius of curvature of the test object (concave/convex): 50 mm (with stabilizing ring: 10 mm)

## Additional Information

---

No.	KP-4403
Manufacturer (Brand)	KERN
EAN	4058072140250
Transport temperature	Room temperature
Manufacturer	CORE

