



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



neolab® XS® pH 5 Tester Kit

€124.00
plus VAT &
Shipping

Product Images



Description

Portable pH meter waterproof IP67

PH 1 meter series with fixed and non-replaceable electrode

PH 5 meter series with replaceable electrode

- Resolution 0.1 pH with microprocessor and fixed sensor
- Calibration with key for 1 or 2 points (selection of pH 4, 7, 10)
- Large LCD display with indication of buffers used for calibration and measurement stability
- Automatic temperature compensation
- Automatic shutdown
- Messages for self-diagnosis: batteries, errors in calibration
- Power supply 2 x 1.5V AAA batteries, also compatible with rechargeable batteries
- The ECO PACK includes: additional glass for calibration, carrying strap, quick reference guide and 2 x 1.5V AAA batteries.

Measuring range: 0.0 ... 14.0 pH (pH 0.1). Working temperature: 0..50 ° C

Additional Information

No.	4-3073
Manufacturer (Brand)	neoLab
EAN	4058072190583
Transport temperature	Room temperature
diameter	0,1 mm
Color	green
Temp MAX	60 °C
Temp MIN	0 °C
Length	200 mm
Display (reading, setting)	graphic display
Weight	0.11 kg
Resolution pH	0.01 pH
Resolution °C	0.1 °C
(Combined) functions	pH meter thermometer
Energy supply	Battery
pH MAX	14.0 pH
pH MIN	0.0 pH
Measuring unit	pH mV °C
Measuring accuracy pH	0.01 pH
Measuring accuracy °C	0.2 °C
Voltage MAX	1000.000000 mV
Voltage MIN	-1000.000000 mV
Type battery	1.5V AAA
Type sensor	XS Standard for tester

