




neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e


Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Brand Dispensette® S, Digital, 0.2–2.0 ml

€446.30
plus VAT &
Shipping

Product Images



Description

Bottle top dispenser with a wide range of applications, DE-M marked and autoclavable (121 °C).

The ejection valve with safety ball minimizes the risk of accidental splashing of the medium. With swivel screw cap, rotatable valve block (360 °) and new valve system without additional sealing rings.

Accuracy:

$\leq \pm 0.5 \%$ (3-0715 = $\leq \pm 1.0 \%$)

Coefficient of variation:

$\leq \pm 0.1 \%$ (3-0715 = $\leq \pm 0.2 \%$)

Adjustment to "Ex". Based on the nominal volume of the device.

Scope of delivery: polypropylene adapter, telescopic suction tube, installation wrench, quality certificate.

Digital version

- digital volume display
- adjustment without tools by Easy Calibration technique
- with backflow valve for fast, bubble-free venting

Additional Information

No.	BN-1345
Manufacturer (Brand)	Brand
old neoLab article no.	3-0723
EAN	4058072207168
Transport temperature	Room temperature
Volume MAX	2 ml
Volume MIN	0.2 ml
Display (reading, setting)	digital
Dispenser properties	with rotatable valve block (360°) with certification with backflow valve with adapter
Functionality	mechanical
Model Bottle Top Dispenser	Fire Dispensette S
Resolution Bottle Top Dispenser	0.2 to 2.0 ml: 0.01 ml
Scope of delivery	BRAND Dispensette S® Digital, bottle top adapter 1 x GL45, 1 x GL32, 1 x GL28, 1 x S40, 1 x telescopic suction tube, 1 x return tube, installation wrench, quality certificate, operating instructions
Correctness at Vol. MAX	0.005
Type Bottle Top Dispenser	Dispenser (digital)
Type certificate	Declaration of conformity (standardization)
Coefficient of variation at Vol. MAX	0.001
for thread/DM	GL 45
adjusted to	"ex"

