



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e


Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Brand Dispensette® S, Analog, 2.5-25 ml

€448.70
plus VAT &
Shipping

Product Images



Description

Bottle top dispenser with a wide range of applications, DE-M marked and autoclavable (121 °C).

The ejection valve with safety ball minimizes the risk of accidental splashing of the medium. With swivel screw cap, rotatable valve block (360 °) and new valve system without additional sealing rings.

Accuracy:

$\leq \pm 0.5 \%$ (3-0715 = $\leq \pm 1.0 \%$)

Coefficient of variation:

$\leq \pm 0.1 \%$ (3-0715 = $\leq \pm 0.2 \%$)

Adjustment to "Ex". Based on the nominal volume of the device.

Scope of delivery: polypropylene adapter, telescopic suction tube, installation wrench, quality certificate.

Version Analog

- analog volume display
- quickly adjustable dosing volume
- easy adjustment with adjustment key

Additional Information

No.	BN-1328
Manufacturer (Brand)	Brand
old neoLab article no.	3-0719
EAN	4058072206994
Transport temperature	Room temperature
autoclavable at 121°C	Yes
Volume MAX	25 ml
Volume MIN	2.5 ml
Display (reading, setting)	analog
Dispenser properties	with rotatable valve block (360°) with certification with adapter
Functionality	mechanical
Model Bottle Top Dispenser	Fire Dispensette S
Division	0.5 ml
Scope of delivery	BRAND Dispensette S® Analog, bottle top adapter 1 x GL45, 1 x GL32, 1 x GL28, 1 x S40, 1 x telescopic aspiration tube, installation wrench, quality certificate, operating instructions
Material valve spring	Platinum Iridium
Correctness at Vol. MAX	0.005
Type Bottle Top Dispenser	Dispenser (analog)
Type certificate	Declaration of conformity (standardization)
Coefficient of variation at Vol. MAX	0.001
for thread/DM	GL 45
adjusted to	"ex"

