



neolab Migge GmbH  
Rischerstr. 7-9  
69123 Heidelberg  
Deutschland  
+49 (0)6221 /  
8442-44  
<https://www.neolab.de>  
e

Umsatzsteuer-  
Identifikationsnummer  
:  
DE 143 450 657



## Brand Dispensette® S, Analog, 5.0-50 ml

**€493.20**  
**plus VAT &**  
**Shipping**

### Product Images



## Description

---

Bottle top dispenser with a wide range of applications, DE-M marked and autoclavable (121 °C).

The ejection valve with safety ball minimizes the risk of accidental splashing of the medium. With swivel screw cap, rotatable valve block (360 °) and new valve system without additional sealing rings.

Accuracy:

$\leq \pm 0.5 \%$  (3-0715 =  $\leq \pm 1.0 \%$ )

Coefficient of variation:

$\leq \pm 0.1 \%$  (3-0715 =  $\leq \pm 0.2 \%$ )

Adjustment to "Ex". Based on the nominal volume of the device.

Scope of delivery: polypropylene adapter, telescopic suction tube, installation wrench, quality certificate.

### Version Analog

- analog volume display
- quickly adjustable dosing volume
- easy adjustment with adjustment key

## Additional Information

|                                      |   |
|--------------------------------------|---|
| No.                                  | BN-1330   |
| Manufacturer (Brand)                 | Brand   |
| old neoLab article no.               | 3-0720  |
| EAN                                  | 4058072207014   |
| Transport temperature                | Room temperature  |
| autoclavable at 121°C                | Yes   |
| Volume MAX                           | 50 ml   |
| Volume MIN                           | 5 ml  |
| Display (reading, setting)           | analog  |
| Dispenser properties                 | with rotatable valve block (360°) with certification with adapter   |
| Functionality                        | mechanical  |
| Scope of delivery                    | BRAND Dispensette S® Analog, bottle top adapter 1 x GL45, 1 x GL32, 1 x GL28, 1 x S40, 1 x telescopic aspiration tube, installation wrench, quality certificate, operating instructions |
| Material valve spring                | Platinum Iridium  |
| Model Bottle Top Dispenser           | Fire Dispensette S  |
| Correctness at Vol. MAX              | 0.005   |
| Division                             | 1 ml  |
| Type Bottle Top Dispenser            | Dispenser (analog)  |
| Type certificate                     | Declaration of conformity (standardization)   |
| Coefficient of variation at Vol. MAX | 0.001   |
| for thread/DM                        | GL 45   |
| adjusted to                          | "ex"  |

