



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Hirschmann® Dispenser 0.4 to 2.0 ml

€362.00
plus VAT &
Shipping

Product Images



Description

High-precision, variably adjustable bottle dosing unit for reproducible dosing of liquids. Very easy and safe volume setting by turning the scale ring.

Steam sterilizable up to 121°C, also completely assembled. With high purity ceramic piston Al₂O₃. The ceramic piston guarantees: no abrasion, no swelling, no thermal problems. Suction and discharge tubes made of PTFE.

With quality certificate, conformity certified.

Scope of delivery

Complete with screw thread A 32 and adapters for A 28, 45 and S 40.

Order No. 3-0932

Variable volume setting

Accessories: Square bottle, brown (Order No. 3-0941 and 3-0942)

Dispenser bottle, round, brown (Order No. 3-0943)

Additional Information

No.	NH-1306
Manufacturer (Brand)	Hirschmann
old neolab article no.	3-0932
EAN	4058072336493
Transport temperature	Room temperature
autoclavable at 121°C	Yes
Volume MAX	2 ml
Volume MIN	0.4 ml
Display (reading, setting)	analog
Dispenser properties	with certification with back metering valve
Functionality	mechanical
Model Bottle Top Dispenser	Hirschmann-ceramus classic
Division	0.05 ml
Scope of delivery	Hirschmann-ceramus® classic bottle-top dispenser fixed or variable, bottle adapter 1 x GL45, 1 x GL32, 1 x GL28, 1 x S40, quality certificate, operating instructions
Material valve spring	Stainless steel
Correctness at Vol. MAX	0.006
Type Bottle Top Dispenser	Dispenser (analog)
Type certificate	Declaration of conformity (standardization) calibration certificate from manufacturer
Coefficient of variation at Vol. MAX	0.002
for thread/DM	GL 32 GL 45 S 40
adjusted to	"ex"

