



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Lauda® Puridest PD 2 R water still 230 V, 50/60 Hz

€1,770.00
plus VAT &
Shipping

Product Images



Description

LAUDA Puridest PD 2 R Water distillation apparatus 230 V; 50/60 Hz Performance features: Mono distiller (fully automatic) with reservoir, suitable for wall mounting and tabletop installation Reservoir for distillate holds twice the hourly capacity of the apparatus Distillate withdrawal tap with continuous and jog position Condenser (cooling coil) in the reservoir, easily replaceable Solenoid valve for controlling the water supply Energy saving by distilling the heated cooling water Water saving by automatic shut-off. Unnecessary water consumption is avoided Distilling bubble easily accessible for cleaning purposes CO₂ degassing opening at the condenser Electronic contamination monitoring of the distilling bubble with distillation stop and visual cleaning indication Automatic refilling of the reservoir after distillate withdrawal, controlled by electronic level detection Thermostatic low-water cut-out. Tubular heating element, distillation bubble, reservoir and condenser made of stainless steel Housing made of galvanized sheet steel, powder-coated Housing design double-walled Technical data: Conductance mono distillate at 25°C: 2.3 µS/cm Production capacity: 2 L/h Tank volume: 4 L Heating capacity max.: 1.5 kW Power consumption max.: 1.5 kW Cooling water consumption: 0.5 L/min Pressure difference cooling water min.: 3 bar Maximum pressure cooling water: 7 bar Water cooling Inlet for hose: 1/2 " Water cooling Outlet for hose: 3/4 " Dimensions (WxDxH): 540 x 290 x 420 mm Weight: 16 kg Ambient temperature range: 10 ... 40 °C Mains supply: 230 V; 50/60 Hz Mains plug: Mains cable with angled Schuko plug (CEE7/7)

Additional Information

No.	LA-1013
Manufacturer (Brand)	Lauda
Transport temperature	Room temperature

