



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Bandelin® SONOREX TECHNIK FA 110 Filtration

€4,837.00
plus VAT &
Shipping

Product Images



Description

The FA filter unit is used to filter out dirt particles from the cleaning solution and enables the service life of the ultrasonic bath to be extended from a volume of 13 liters. The cleaning system is suitable for filtering aqueous cleaning media up to a maximum liquid temperature of 70 °C. The FA filter unit consists of two filter housings made of polypropylene (PP) and a magnetically coupled centrifugal pump, which are mounted together on a console made of stainless steel sheet. The pre-filter serves to protect the pump from coarse contamination. The fine filter is used for depth filtration. Further equipment includes a pressure switch, a ball valve, a switch box with ON button, a main switch and 2 meters of connection cable with safety plug. - The pressure switch switches off the pump when the fine filter is clogged. The - fine filter can then be replaced. - The ball valve can be used to adjust the flow rate. - The pump of the filter unit must be below the liquid level of the tub. Mains connection: 230 V EU plug

Additional Information

No.	BL-0789
Manufacturer (Brand)	Bandelin
Transport temperature	Room temperature

