




neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Lauda® Proline PVL 15 see-through thermostat 230 V, 50/60 Hz

€12,600.00
plus VAT &
Shipping

Product Images

Description

LAUDA Proline PVL 15 see-through thermostat 230 V; 50/60 Hz Performance features: Bath/circulator thermostat with state-of-the-art microprocessor technology and built-in cooling coil Easy-to-read, green LED display for temperature User-friendly menu navigation and simplest 3-button operation EasyUse system for easiest handling and operation of the entire device SelfCheck assistant for system diagnostics Fully electronic continuous controller with PID behavior for internal and external control PowerAdapt system for optimally adapted max. Heating power without power supply overload Low level protection and adjustable overtemperature protection with acoustic alarm for operation with flammable and non-flammable liquids LAUDA Varioflex pump (pressure pump) with 8 selectable power levels Retrofittable with up to 2 additional interface modules (RS 232/485, Profibus, analog or contact modules, Ethernet-USB module) Measuring chamber with 5-layer insulating glass for low temperatures down to -60 °C due to additional cooler Pump connections at the rear and on the side, integrated bypass Bath vessel made of stainless steel (insulated, with carrying handles and drainage tap) Technical data (according to DIN 12876): Working temperature range: 30 ... 100 °C Working temperature range with water cooling: 20 ... 100 °C Operating temperature range: -60 ... 100 °C Ambient temperature range: 5 ... 40 °C Temperature stability: 0.01 ± K Heating power max.: 2.9 kW Current consumption: 13 A Power consumption max.: 3 kW Pump flow max. (pressure): 25 L/min Bath volume min. / max.: 11.0 / 15.0 L Bath size (WxDxH): 230 x 135 x 320 mm Dimensions (WxDxH): 506 x 282 x 590 mm Weight: 35 kg Power supply: 230 V; 50/60 Hz Power plug: power cord with angled plug (BS1363) Standard accessories: 4 union nuts, 4 sealing plugs 2 hose olives 13 mm for pump connection 2 hose olives for cooling coil

Additional Information

No.	LA-2448
Manufacturer (Brand)	Lauda
Transport temperature	Room temperature

