



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Lauda® Versafreeze VF 70085 Freezer 230 V, 50 Hz

€16,100.00
plus VAT &
Shipping



Description

LAUDA Versafreeze VF 70085 Freezer 230 V; 50 Hz Performance Features: Laboratory freezer with reliable monitoring and highly efficient insulation for long-term storage and quality assurance Convenient 4,3" touchscreen control panel with digital display for entering and retrieving all safety-relevant values Limit values for overtemperature and undertemperature alarm adjustable Protection against unauthorized access to setpoints through password-protected user management Electronic alarm system and potential-free alarm contact for connection to an in-house alarm system or the central control system (CCS) Maintenance of display and alarm functions even in the event of power failure (battery buffering). Interior completely made of stainless steel Seven interior compartments, each protected against cold loss by an insulating door For long-term storage and quality assurance of organic substances and other materials Built-in data logger for storage of temperature and alarm data IIOT ready via high-performance Ethernet interface RS 485 interface for trouble-free data transfer A closely laid cooling coil ensures high freezing speed, excellent temperature homogeneity and constancy throughout the usable space Energy-efficient refrigeration technology reduces heat dissipation into the environment Energy-saving, energy-saving, maintenance-free refrigeration system with fully hermetic high-performance compressors Environmentally friendly and future-proof operation with natural refrigerants The high-quality vacuum insulation reduces the wall thicknesses and thus creates more storage space with the same footprint Two feed-throughs, inner diameter 13 mm, as standard, for the insertion of control sensors, e.g. type Pt100 Magnetic sealing system reliably prevents freezing of the door/cover seals Included options: Interior equipment with 5 stainless steel drawers Insulating panels to prevent cold loss, with stainless steel handles Technical data: Working temperature range: -86 ... -50 °C Ambient temperature range: 15 ... 28 °C Usable space: 731 L Usable space dimensions (WxDxH): 738 x 750 x 1320 mm Dimensions (WxDxH): 980 x 1165 x 1965 mm Cooling time: from 20 °C to -86 °C in 7 h Thawing time: from -86 °C to 0 °C in 25 h Energy consumption: 15.5 kWh/d at -86 °C Refrigerant stage 1: R-290 (GWP 3); 0.145 kg; 0.0 t CO₂-eq Refrigerant stage 2: R-170 (GWP 3); 0.090 kg; 0.0 t CO₂-eq Mains supply: 230 V; 50 Hz Mains plug: mains cable with angled Schuko plug (CEE7/7)

Additional Information

| | |
|-----------------------|------------------|
| No. | LA-2731 |
| Manufacturer (Brand) | Lauda |
| Transport temperature | Room temperature |

