



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



WELCH® Diaphragm pump MP 065 E 90...260VAC /18VDC

€576.00
plus VAT &
Shipping

Product Images



Description

Suction capacity 0.7 m³/h Suction/pressure connection Hose shaft DN6, for hose inner diameter 6 mm Max.
Overpressure 0.3 bar Working temperature 10 to 60 °C Voltage power supply 90-240V 50/60Hz AC Motor voltage 18 VDC Diaphragm pumps for physical applications - type MP - are compact, practical and functionally oil-free pumps. They are manufactured in single or multi-stage design - with regulated (ecoflex) and unregulated suction power. The long service life of the pumps speaks for itself. Fields of application: - physical applications - dry-oil-free in the rough vacuum range - alternative to water jet pumps - degassing processes - manipulation technology - as backing pump
Scope of delivery: diaphragm pump complete with on/off switch, integrated motor protection switch, hose shafts for hose inner diameter 8 mm or small flanges DN 16 KF and optimized swing feet. Note: Order country-specific device connection cable separately to the pump, see chapter Device accessories. Successor to U2050C-02

Additional Information

No.	WL-0204
Manufacturer (Brand)	WELCH
VGKL number	109241112
Transport temperature	Room temperature

