




neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Thermo Scientific Bottle/Tube Roller

€1,260.00
plus VAT &
Shipping

Product Images

Description

Bottle/Tube Roller Suitable for rolling test tubes and bottles of various sizes, with digital speed control from 1 to 80 rpm, can also be used safely in CO₂ and/or humid environments. Outer height (anglo): 2.8 in. Outer height (metric): 72 mm Shipping weight (Anglo): 14.3 lbs. Shipping Weight (metric): 6.5 kg Outer Width (Anglo-American): 14.9 in. Certification/Compliance: CE, cCSAus Dimensions (LxWxH): 14.2 in. x 2.8 in., 360 mm x 72 mm Connector Type: cable set with various connectors Speed: 1 rpm to 80 rpm Type: rollers Speed Range: 1 to 80 rpm Temperature Range (anglo): 39.2 °F to 140 °F Temperature range (metric): 4° to 60 °C Load capacity (Anglo-American): 14.3 lbs. Load capacity (metric): 6.5 kg Outer length (Anglo-American): 14.2 in. Outer length (metric): 360 mm Outer width (metric): 378 mm Voltage: 100 V to 240 V AC Hertz: 50/60 Hz Active Power: 10 W Diameter (Anglo-American) Roller: 1.1 in. Diameter (metric) Roller: 28 mm Max. Cylinder diameter (anglo): 1e; 4.72 in. Max. Bottle diameter (metric): 1e; 120 mm Number of rollers: 6 rollers as standard, up to 11 more can be added Relative humidity: 1e; 95% Stackable: two units on top of each other with optional stacking kit Timing range: 0 to 999 min or continuous operation Warranty and service: 2 years Tolerance: moisture resistant to 1e; 95% humidity as well as CO₂/sub resistant Electrical requirements: 100 V to 240 V ac at 50/60 Hz Dimensions (L x W x H) external: 14.2 x 14.9 x 2.8 in. (360 x 378 x 72 mm) Unit Size: Each

Additional Information

No.	LD-2769
Manufacturer (Brand)	Thermo Scientific
Transport temperature	Room temperature

