




neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Thermo Scientific Barnstead™ GenPure™ xCAD Plus

€12,500.00
plus VAT &
Shipping

Product Images

Description

Barnstead™ GenPure™ xCAD Plus Dispense Type 1 ultrapure water from up to three dispensers simultaneously with the Thermo Scientific Barnstead GenPure xCAD Plus high purity water treatment system. Frequency: 50/60 Hz Feedwater Connector: 3/4 in. Product Water Type: Type 1 TOC Monitor with UV Intensity Monitoring: Yes Type: Water Treatment System Electrical Resistance: 18.2 Mohm.cm at 25 °C Conductivity: 0.055µS/cm Flow rate: Up to 2 l/min TOC (Total Organic Carbon): 1 to 5 ppb Endotoxin concentration: 0.001 EU/mL Bacterial content: It;0.01 CFU/mL Particle 0.2 µm/mL: It;1 Remote dispenser: Yes Feed water monitoring: Integrated Height (Anglo-American): 24 in. Width (anglo): 14.6 in. Operating Pressure: 0.1 to 6 bar Voltage: 90/240 V Temperature Range (metric): 2 °C° to 35 °C° Depth (Anglo-American): 13 in. Description: Barnstead GenPure xCAD Plus UV/UF – TOC (wall version) Power Consumption: 0.1 kW Electrical Requirements: 90/240 V 50/60 Hz Unit Size: Each

Additional Information

No.	LD-1302
Manufacturer (Brand)	Thermo Scientific
VGKL number	108662227
Transport temperature	Room temperature

