



Thermo Scientific Barnstead™ Pacific™ TII

Product Images

Description

Barnstead™ Pacific™ TII Conversion of tap water to Type 2 ultrapure water with the automatic and cost-effective Thermo Scientific™ Barnstead™ Pacific™ TII water treatment system. Frequency: 50/60 Hz Feedwater Connector: 3/4 in. NPT Type of Product Water: Type 2 TOC Monitor with UV Intensity Monitoring: No Type: Water Treatment System Electrical Resistance: 10 to 1 Mohm.cm at 25 °C Conductivity: 0.067 to 0.1µS/cm Daily delivery: 20 to 200 l Feed water source: cone Flow rate: 7 l/h at 10 °C TOC (Total Organic Carbon): 30 ppb Bacterial content: 99% Particle 0.2 µm/ml: lt;1 pM / ml Feed water monitoring: No Feed water pressure: 1 to 6 bar Operating pressure: 2 to 6 bar Voltage: 90/240 V Temperature range (metric): 2 °C° to 35 °C° Bacterial retention: 99% Description: Pacific TII 7 Permeate capacity: 7 l/h at 10 °C Electrical requirements: 90/240 V 50/60 Hz Unit Size: Each

Additional Information

No.	LD-1259
Manufacturer (Brand)	Thermo Scientific
VGKL number	108662107

