




neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Thermo Scientific Barnstead™ Smart2Pure™

€6,780.00
plus VAT &
Shipping

Product Images

Description

Barnstead™ Smart2Pure™ Conversion of tap water to both ASTM Type 1 water and Type 2 water with the compact, all-in-one Thermo Scientific™ Barnstead™ Smart2Pure™ Water System. Frequency: 50/60 Hz Feedwater Connector: 3/4 in. NPT Type of Product Water: Type 1 and 2 TOC Monitor with UV Intensity Monitoring: No Type: Water Treatment System Electrical Resistance: Type 1: 18.2 Mohm.cm at 25 °C; Type 2: 10 to 15 Mohm.cm at 25 °C Conductivity: Type 1: 0.055µS/cm ; Type 2: 0.067 to 0.1µS/cm Feed water source: cone Flow rate: 0.6 l/min TOC (Total Organic Carbon): 1 to 5 ppb Endotoxin concentration: 0.005 EU/mL Bacterial content: It; 1CFU/mL Particle 0.2 µm/mL: It;1 Remote dispenser: No Feed water monitoring: No Feed water pressure: 1 to 6 bar Operating pressure: 1 to 6 bar Bacterial retention: 99% Permeate capacity: 3 l/h at 10 °C Power consumption: 0.06 kW RO flow rate: 3 l/h Electrical requirements: 100/240 V 50/60 Hz Includes: Internal 6 l tank with vent filter, RO/pretreatment cartridge, ultrapure water cartridge, sterile 0.2 µm filter, pressure regulator and UV lamp. Unit Size: Each

Additional Information

No.	LD-1245
Manufacturer (Brand)	Thermo Scientific
VGKL number	108662032
Transport temperature	Room temperature

