



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Lauda® Hydro H 16 A water bath 230 V, 50/60 Hz

€1,560.00
plus VAT &
Shipping

Product Images

Description

LAUDA Hydro H 16 A Water bath 230 V; 50/60 Hz Performance features: Water bath with easy operation TFT display with clear indication of all process data Setting and display of temperature values in steps of 0.1°C. Setting of timer time values in hours (h) and minutes (min). Membrane keypad with concise symbols Digital setpoint adjustment Adjustable trigger points for over- and undertemperature alarm up to max. +/- 10 K Temperature display switchable from °C to °F 1-point temperature controller Visual and audible alarm for low water, over/under temperature and sensor break/short circuit Electronic function monitoring of temperature controller Three application-specific timer functions With integrated circulation system to improve spatial temperature constancy Bath body, Cover frame, sieve bottom and heater made of stainless steel Bath vessel with drain cock Heat-insulating lid made of stainless steel, double-walled with inner curvature prevents condensate from dripping back into the vessels Lid and sieve bottom as standard Technical data: Working temperature range: 25 ... 100 °C Ambient temperature range: 10 ... 40 °C Temperature stability: 0.1 ± K Heating power max.: 1.5 kW Bath size (WxDxH): 400 x 245 x 165 mm Bath volume min. / max.: 7.5 / 13.9 L Dimensions (WxDxH): 500 x 440 x 345 mm Weight: 16 kg Power supply: 230 V; 50/60 Hz Power plug: Power cord with plug (NBR 14136)

Additional Information

No.	LA-1690
Manufacturer (Brand)	Lauda
Transport temperature	Room temperature

