

neoLab Migge GmbH Rischerstr. 7-9 69123 Heidelberg Deutschland +49 (0)6221 / 8442-44 https://www.neolab.d e Umsatzsteuer-Identifikationsnummer :

DE 143 450 657



Testo® 330-2 LL Flue gas measuring instrument - Chimney sweep set

Price on request plus VAT & Shipping

Product Images



Description

The testo 330 LL is the professional flue gas analyzer that meets the highest demands and is up to any measurement task involving the heating system. The sensors in the instrument family have a service life of up to 6 years. This means that at least one sensor change is not required during the typical service life. In addition, Testo provides a 4-year warranty without a maintenance contract. Choose from our extensive range of exhaust gas probes, which often replace an additional measuring device. With its automatic fresh air dilution from 8,000 ppm CO, the testo 330-2 LL offers a high level of safety when adjusting solid fuel and oil systems and protects the sensors up to 30,000 ppm CO content. The complete set consists of the testo 330-2 LL measuring instrument with H2-compensated CO measuring cell, a modular 300 mm flue gas probe, a 190 mm combustion air temperature sensor and a power supply unit. Choose a device that really supports you! Features of the testo 330-2 LL: - For CO measurement, automatic dilution takes place from 8,000 ppm up to min. 30,000 ppm CO - Integrated draft and gas zeroing without probe removal: probe can remain in the flue during zeroing - Extensive probe program offers great flexibility - Logger function for simple longterm recording of the measurement course - Pressure measurement up to 300 mbar - Self-definable fuels - TÜVtested according to 1. BImSchV / EN 50379 part 2 for O2, °C; hPa and CO with H2 compensation - TÜV approved solid fuel measurement for O2 and CO by optional solid fuel set - Strong memory management: 500.000 measured values - IrDa-/Bluetooth-interface for data transfer to pocket PC / laptop / printer - ZIV-driver for all common industry software

Additional Information

No.	TO-0555
Manufacturer (Brand)	Testo
Transport temperature	Room temperature

