



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Testo® 330-2 LL v2010 - Exhaust gas analyzer with Bluetooth and COH2 cell

**Price on
request
plus VAT &
Shipping**

Product Images



Description

The testo 330-2 LL is the professional flue gas analyzer that meets the highest demands and is up to any measurement task involving the heating system. The sensors in the instrument family have a service life of up to 6 years. This means that at least one sensor change is not required during the typical service life. In addition, Testo provides a 4-year warranty without a maintenance contract. Choose from our extensive range of exhaust gas probes, which often replace an additional measuring device. With its automatic fresh air dilution from 8,000 ppm CO, the testo 330-2 LL offers high safety when adjusting solid fuel and oil systems and protects the sensors up to 30,000 ppm CO content. Choose an instrument that really supports you! Features of the testo 330-2 LL: For CO measurement, automatic dilution takes place from 8,000 ppm up to min. 30,000 ppm CO Integrated draft and gas zeroing without probe removal: probe can remain in the flue during zeroing Extensive probe program offers great flexibility Logger function for simple long-term recording of the measurement process Pressure measurement up to 300 mbar Self-definable fuels TÜV-tested according to 1. BImSchV / EN 50379 Part 2 for O₂, °C; hPa and CO with H₂ compensation TÜV-tested solid fuel measurement for O₂ and CO through optional solid fuel set Strong memory management: 500,000 measured values IrDa/Bluetooth interface for data transfer to pocket PC / laptop / printer ZIV driver for all common industry software

Additional Information

No.	TO-0821
Manufacturer (Brand)	Testo
Transport temperature	Room temperature

