



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



Brand® Transferpettor type Fix, DE-M, 1 µl, with glass capillary

€212.80
plus VAT &
Shipping

Product Images



Description

Where air cushion pipettes come up against natural limits is where the strength of the Transferpettor pipette lies. Whether viscous or thin liquids, whether foaming or with high vapor pressure, the Transferpettor pipette dispenses such liquids with maximum precision. The solution for difficult cases! The functional principle of the Transferpettor pipette is direct displacement: Unlike air cushion pipettes, the piston of the direct displacement pipette has direct contact with the liquid to be pipetted. The fixed piston always wipes the walls of the capillaries/tips cleanly – down to literally the last drop that clearly leaves the opening. This principle ensures exactly reproducible results, regardless of the pipetting speed. The capillaries or tips do not have to be discarded after each pipetting step, as residual wetting is minimal and can usually be neglected. The Transferpettor pipette is suitable for media with: density up to 13.6 g/cm³, viscosity up to 140,000 mm²/s, vapor pressure up to 500 mbar. Working temperature range: 15 °C to 40 °C

Additional Information

No.	BN-1550
Manufacturer (Brand)	Brand
VGKL number	144971842
Manufacturer EAN	4033378300270
Transport temperature	Room temperature

