



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



B-SAFETY® safety eye shower with catch basin for wall mounting surface-mounted

**€536.00
plus VAT &
Shipping**

Product Images



Description

ClassicLine safety eye shower with catch basin for wall mounting surface-mounted - wall flange with 4 mounting holes made of stainless steel, chemical-resistant green powder-coated, water connection 3/4-inch female - plug-in system X6 made of stainless steel 3/4-inch for easy installation and alignment of the shower, chemical-resistant green powder-coated, water connection 3/4-inch-IG - connection pipe 1/2-inch stainless steel with plug-in connection X8, chemical-resistant green powder-coated, length 60 mm - integrated automatic flow regulator 14 liters / minute for a standard-compliant spray pattern at a specified working range of 2,5 to 5 bar flow pressure - 1/2-inch stainless steel ball valve, with PUSH lever operation, DIN-DVGW tested and approved - steel operating panel, chemical-resistant green powder-coated, length 240 mm, with large "PUSH" signal, photoluminescent according to DIN 67510 - stainless steel collecting basin, diameter 275 mm, chemical-resistant green powder-coated, drain connection 1 1/4-inch male - wide-jet high-performance shower heads, with plastic spray plate, low calcification, incl. rubber protection and tightly closing dust cover. Rubber protection and tightly closing dust cover with hinged mechanism, mounted over distribution fork - information sign for eye shower according to DIN EN ISO 7010 and ASR A1.3, self-adhesive PVC foil, dimensions 100 x 100 mm, recognition distance 10 meters - height 220 mm, projection 385 mm, total width incl. lever Lever 425 mm - mounting height 860 mm (\pm 200 mm) - according to BGI/GUV-I 850-0, DIN 1988 and DIN EN 1717 - according to ANSI Z358.1-2014 and DIN EN 15154-2:2006 - DIN-DVGW tested and approved

Additional Information

No.	FG-0021
Manufacturer (Brand)	B-SAFETY
Transport temperature	Room temperature

