



neolab Migge GmbH  
Rischerstr. 7-9  
69123 Heidelberg  
Deutschland  
+49 (0)6221 /  
8442-44  
<https://www.neolab.de>  
e

Umsatzsteuer-  
Identifikationsnummer  
:  
DE 143 450 657



## qpore® Syringe Filter, PES, sterile, 0.45 µm, Ø 13 mm

**€179.00**  
**plus VAT &**  
**Shipping**

### Product Images



## Description

---

This **sterile qpore® syringe filter** has a hydrophilic membrane made of **PES** with a high mechanical and chemical resistance with minimal protein absorption. An excellent flow rate makes it optimal for sterile filtration, clear filtration and cell removal under sterile conditions. The effective filtration area of this syringe filter is 4.90 cm<sup>2</sup>. The sturdy polypropylene filter housing is pressure resistant up to a maximum of 5.0 bar, enabling rapid filtration.

### Features:

- Low dead volume
- Stable at pH 1-14
- DNA-, DNase-, RNase-, Pyrogen-free
- **Luer connections:** Luer lock female, **Luer cone** male
- No risk of mix-up due to labeling (membrane type, pore size)
- The syringe filters are **individually sterile packed to 100 pieces**.

## Additional Information

---

|                        |                             |
|------------------------|-----------------------------|
| No.                    | 6-0125                      |
| Manufacturer (Brand)   | qpore                       |
| EAN                    | 4058072173210               |
| Transport temperature  | Room temperature            |
| Color                  | White                       |
| Material               | Polypropylene (PP)          |
| sterile                | Yes                         |
| suitable for           | Syringes                    |
| Filter properties      | individually packed sterile |
| MAX operating pressure | 6 bar abs.                  |
| DM outside             | 13 mm                       |
| Area diaphragm         | 1.09 cm <sup>2</sup>        |
| Fluid behavior         | hydrophilic                 |
| Material membrane      | Polyethersulfone (PES)      |
| Pore size              | 0.45 µm                     |
| TBST MAX               | 90 °C                       |
| Type Connection Output | Luer lock male              |
| Type Connection Input  | Luer lock female            |
| Type filter            | Syringe pre-filter          |
| for medium             | Liquids                     |

