



neolab Migge GmbH
Rischerstr. 7-9
69123 Heidelberg
Deutschland
+49 (0)6221 /
8442-44
<https://www.neolab.de>
e

Umsatzsteuer-
Identifikationsnummer
:
DE 143 450 657



**neochrom® aluminum flare cap, 20 mm, bright
rolled 10mm hole, (pack of 100 pieces) silicone
white PTFE beige, 45° shore A, 3.2 mm**

**€57.60
plus VAT &
Shipping**

Product Images



Description

Flared closures, assembled with septa.

Septum silicone/PTFE

Temperature resistant from -60°C to 200°C

For easy penetration

For critical analyses

Thickness: 3.0 mm

Silicone white/PTFE beige = AGILENT quality, thickness 3.2 mm

Additional Information

No.	7-0831
Manufacturer (Brand)	neochrom
EAN	4058072030704
Transport temperature	Room temperature
Color	silver
Type closure/ lid	Flare cap
Closures and lids features	with mounted septum suitable for autosampler cap with septum cap autoclavable
DM Hole	10 mm
Quantity components	two
Hardness	45 shore A
Material gasket / septum	Silicone Polytetrafluoroethylene (PTFE)
Closure / lid properties	with hole with mounted septum
DM Closure	20 mm
Thickness septum	3.2 mm
Material closure/ lid	Aluminum
TBST MAX Septum	200 °C
TBST MIN Septum	-60 °C
Type flare cap	Flared cap. standard
for the autosampler model (If your AS does not appear here, please ask the AS manufacturer directly for the compatibility of the cap with your AS)	Agilent G1888A Agilent HS 7694 Carlo Erba HS850 Dani HS 39.50 Dani HS 86.50 Fisons HS850 HTA HT200H Perkin Elmer HS6 Thermo Scientific HS850 Thermo Scientific HS2000 Thermo Scientific TriPlus HS Thermo Scientific TriPlus SMPE Teledyne Tekmar HT3 Varian CP

